ARCTOS
CONSTRUCTION SYSTEMS™

EP426/EP520

CONCRETE PLACER + LINE MOVING SYSTEM



PORTABLE CONCRETE PLACEMENT WITH REACH, MANEUVERABILITY AND SINGLE-OPERATOR CONTROL

The EP Series carries forward the proven E-Z Placer concept as a self-propelled concrete placer and line-moving system in one portable unit. The current EP426/EP520 platform combines a two-section 27 ft boom with 360° main- and tip-boom swivel, agile four-wheel independent steering, all-wheel drive, and 100% wireless single-operator control with manual backup.

Powered by a 13 HP Honda GX390 gasoline engine, the compact 60 in wide, 4,000 lb platform fits through most commercial doorways and transports with a 3/4 ton pickup and trailer. EP426 and EP520 are the 4 in and 5 in delivery configurations.

4,000 LB	60”	27’	360°
MACHINE WEIGHT	MACHINE WIDTH	BOOM REACH	BOOM COVERAGE

KEY FEATURES

Two-Section 27ft Boom
360° coverage with 16 ft main boom and 11 ft continuously swiveling tip boom

Wireless Single-Operator Control
100% wireless remote operation with machine-mounted manual backup controls

Compact Jobsite Footprint
60 in width fits through most commercial doorways while keeping the platform versatile and portable

All-Wheel Drive + Steering
All-wheel drive with agile four-wheel independent steering for jobsite maneuverability

4” and 5” Delivery Options
EP426 is the 4 inch configuration and EP520 is the 5 inch configuration; rear or side pump connection

Easy Transport
Transport with a 3/4 ton pickup truck and trailer; current trailer-mode length is 27 ft.

ARCTOS
CONSTRUCTION SYSTEMS™



	EP426	EP520
Engine	13 HP Honda GX390, gasoline	13 HP Honda GX390, gasoline
Machine Size	W-5 ft x L-36 ft 8 in x H-5 ft 6 in	W-6 ft x L-30 ft x H-6 ft 6 in
Machine Weight	4,000 lb (1,814 kg)	4,000 lb (1,814 kg)
Steering System	4 Wheel Independent Steering	4 Wheel Independent Steering
Drive System	All Wheel Drive	All Wheel Drive
Overall Boom Reach	27 ft (8.2 m), 360°	20 ft (6 m), 360°
Main Boom	16 ft, left-right 360° swivel	13 ft, left-right 360° swivel
Tip Boom	11 ft, continuous 360° swivel	7 ft, continuous 360° swivel
Machine Operation Control	100% Wireless + Manual Backup	100% Wireless + Manual Backup
Single Operator Control	Yes	Yes
Delivery Line	4 in (10.2 cm)	5 in (12.7 cm)
Line Pump Connection	Rear or Side	Rear or Side
Transport with Pickup + Trailer	Yes	Yes
Trailer Mode Length	27 ft (8.2 m)	24 ft (7.2 m)

Ready to learn more about the EP Series?

SALES: 812-903-4500 EMAIL: sales@arctoscs.com WEB: arctoscs.com

10/26