ARCTOS
CONSTRUCTION SYSTEMS™

PB16E/PB16LP/PB21/PB4816E
POWER BUGGY SERIES



PROVEN MATERIAL MOVERS BUILT FOR JOBSITE EFFICIENCY

The Power Buggy Series brings the proven legacy of The Original Power Buggy into the Arctos lineup, reinforcing our commitment to innovation, quality, growth, and industry-leading solutions for concrete professionals.

These quick, versatile ride-on material movers are built for efficient work in tight jobsite conditions, combining straightforward controls, strong traction, simultaneous dump-and-drive capability, and model choices for moving concrete, stone, mulch, and more.

Four models provide 16 or 21 cu ft capacity, load ratings up to 3,200 lb, speeds up to 7.25 mph, and gasoline, propane, or electric power options.

3,200 LB
MAX LOAD

16-21 CU FT
CAPACITY

7.25 MPH
TOP SPEED

3 POWER OPTIONS
GAS/PROPANE/ELECTRIC

KEY FEATURES

Simultaneous Dump + Drive
Feather loads smoothly while moving forward or reverse.

Heavy-Duty Hydraulics
Heavy-duty hydraulic pump and two high-efficiency drive motors deliver dependable power.

Jobsite Versatility
Ideal for concrete, stone, mulch, and maneuvering through tight spaces.

Three Power Options
Choose gasoline, propane, or electric power to fit the application.

Operator-Focused Controls
Comfortable platform, clean control panel, and foot-operated dump keep both hands on the steering wheel.

Traction + Reliable Braking
Heavy-duty welded chassis and the industry's largest, highest-efficiency wheel motors support exceptional traction, higher speeds, and more reliable braking.

High Capacity + Speed
Carry material up to 3,200 lb at speeds up to 7.25 mph.

PB16LP Propane Benefits
Lower fuel costs; cleaner exhaust emissions; less carbon build-up; extended engine life; closed fuel system helps inhibit fuel contamination; OSHA, EPA & CARB compliant.

ARCTOS
CONSTRUCTION SYSTEMS™



	PB16E PB16LP	PB21	PB4816E
Wheelbase	43 in (109.2 cm)	43 in (109.2 cm)	43 in (109.2 cm)
Overall Length	103 in (261.6 cm)	101.5 in (257.8 cm)	111 in (281.9 cm)
Overall Width (Single Wheels) Overall Width (Dual Wheels)	35.5 in (90.2 cm) 47 in (119.4 cm)	N/A 47 in (119.4 cm)	N/A 46 in (116.8 cm)
Overall Height	53 in (134.6 cm)	56 in (142 cm)	53 in (135 cm)
Maximum Load	2,500 lbs (1,136 kg)	3,200 lbs (1,455 kg)	2,500 lbs (1,136 kg)
Capacity	16 cu ft (453 L)	21 cu ft (595 L)	16 cu ft (453 L)
Discharge Height	3.5 in (8.9 cm)	5 in (12.7 cm)	7.5 in (19 cm)
Hydraulic Oil (Exxon Nuto #H68)	11.5 qt (11.0 L)	11.5 qt 11.0 L	24 qt (22.7 L)
Speed	7.25 mph (11.67 km/h)	7.25 mph (11.67 km/h)	5.6 mph (9.0 km/h)
Drive	Hydrostatic	Hydrostatic	Electric
Brakes	Hydraulically Controlled	Hydraulically Controlled	Electric
Parking Brake	Mechanical	Mechanical	Automatic Electric Mechanical
Dump	Variable Hydraulic	Variable Hydraulic	Electric
Power	Honda GX390 13 hp E-start Propane	Vanguard B&S 18 hp	Six 12V Deep Cycle Batteries (48V system) Avg Run 13 mi (loaded)
Drive Tires	5.70 × 8 x 19	5.70 x 8 x 19	5.70 × 8 x 19
Steering Tires	4.80 × 8 x 16	4.80 x 8 × 16	4.80 × 8 x 16
Operating Weight	1,260 lbs (571.5 kg)	1,325 lbs (601 kg)Poly 1,480 lbs (671 kg) Steel	1,675 lbs (760 kg)
Shipping Weight	1,360 lbs (616.9 kg)	1,425 lbs (646 kg) Poly 1,580 lbs (717 kg) Steel	1,775 lbs (805.1 kg)

Ready to learn more about the Power Buggy Series?

SALES: 812-903-4500 EMAIL: sales@arctoscs.com WEB: arctoscs.com